



RTS (Residue Tillage Specialist)

EXPANDING YOUR INFLUENCE OVER YIELD LIMITING FACTORS

- The new Salford RTS (Residue Tillage Specialist) is the ideal tool for today's high residue farming methods
- Cut and distribute crop residue while warming the soil to a shallow depth to create an ideal seedbed
- The versatile coil-tech coulters are designed for high speed and low maintenance; the most durable coulters system available

Size	Frame Sections	Number of Coulters	Estimated H.P. Required	Transport Width	Transport Height	Machine Weight	Machine Weight with Harrow Attachments
RTS Coulters Cultivator 7" Spacing							
12'	1	21	70-120	13'3"	No Wings	5,100 lbs	6,250 lbs
16'	3	27	100-160	10'	9'	6,664 lbs	8,200 lbs
18'	3	31	120-180	12'8"	10'8"	7,800 lbs	9,500 lbs
22'	3	37	150-220	12'8"	12'3"	8,900 lbs	11,000 lbs
24'	3	41	180-250	12'3"	13'3"	9,300 lbs	11,600 lbs
27'	3	47	190-270	15'8"	13'	11,000 lbs	13,500 lbs
30'	3	53	210-300	15'8"	14'6"	11,800 lbs	14,700 lbs
36'	3	62	250-350	21'	14'2"	13,250 lbs	16,950 lbs
41'	3	70	280-400	21'	16'6"	14,700 lbs	18,500 lbs
41' *	5	71	280-400	18'9"	13'6"	15,900 lbs	19,700 lbs
50' *	5	85	350-500	19'	14'3"	19,600 lbs	24,400 lbs

*Bi-fold

STANDARD FEATURES

- 20" x 4.5 mm 8 or 13 wave coulters blades
- Hydraulic self-leveling frame and hitch
- Single point depth control
- 4" x 6" frame on all models
- Walking tandems on main and wings
- Single wing wheel on 18 ft
- Duals on 16 ft working width

OPTIONS

- Adjustable tow hitch
- 14" coulters spacing
- Hydraulic lines and quick coupler to tow hitch
- Weight kits - 100 lbs each

- 17" blades in lieu of 20"
- Axle pivot grease bank
- Coulters drop mount track eliminator
- Single wheels on wings
- Tandem wing wheels
- Fertilizer and tillage shanks
- Seeding tubes

RTS USES

- Operate in high moisture conditions
- Spring prep for no-till
- Seedbed preparation
- Incorporate cover crops
- Uniform Residue Distribution
- Stalk chopper ahead of primary tillage
- Incorporate seed-fertilizer-manure-herbicides

- All season uses
- Seeding of cereals and small grains
- Yield gain
- Use as a rotary hoe
- Perfect partner for stripper headers
- Prepare seedbed for double crop soybeans
- Warm soil and release excess moisture
- Compost heavy residue
- Release excess soil moisture
- Improve seedbeds after planting
- Soil preparation for strip till

3 YEAR LIMITED WARRANTY

Salford Farm Machinery is designed and built with longevity and serviceability in mind and is intended to withstand the normal rigors of agricultural use. Please talk to your dealer or call us today at (519) 485-1293 or 1-866-442-1293 for all the details. Features and specifications may change without prior notice. Please read our terms and conditions.

Osceola, Iowa • Ontario, Canada • 1-866-442-1293 • www.salfordmachine.com