

# RTS (Residue Tillage Specialist)

**SALFORD**

## EXPANDING YOUR INFLUENCE OVER YIELD LIMITING FACTORS

- The new Salford RTS (Residue Tillage Specialist) is the ideal tool for today's high residue farming methods
- Cut and distribute crop residue while warming the soil to a shallow depth to create an ideal seedbed
- The versatile coil-tech coulters are designed for high speed and low maintenance; the most durable coulters system available



Size	Frame Sections	Number of Coulters	Estimated H.P. Required	Transport Width	Transport Height	Machine Weight	Machine Weight with Harrow Attachments
RTS Coulters Cultivator 7" Spacing							
12'	1	21	70-120	13'3"	No Wings	5,100 lbs	6,250 lbs
16'	3	27	100-160	10'	9'	6,664 lbs	8,200 lbs
18'	3	31	120-180	12'8"	10'8"	7,800 lbs	9,500 lbs
22'	3	37	150-220	12'8"	12'3"	8,900 lbs	11,000 lbs
24'	3	41	180-250	12'3"	13'3"	9,300 lbs	11,600 lbs
27'	3	47	190-270	15'8"	13'	11,000 lbs	13,500 lbs
30'	3	53	210-300	15'8"	14'6"	11,800 lbs	14,700 lbs
36'	3	62	250-350	21'	14'2"	13,250 lbs	16,950 lbs
41'	3	70	280-400	21'	16'6"	14,700 lbs	18,500 lbs
41'*	5	71	280-400	18'9"	13'6"	15,900 lbs	19,700 lbs
50'*	5	85	350-500	19'	14'3"	19,600 lbs	24,400 lbs

\*Bi-fold frame

### STANDARD FEATURES

- 2 Choices of Blades:
  - 20" x 4.5mm - 8 or 13 wave
- Hydraulic self-leveling frame (4" x 6")
- Hydraulic single point depth control
- Walking tandems on main frame and wings (except as noted below)
  - Duals on main frame 16' model
  - Single wheels on 18' wings
- Tires—Mainframe
  - 12' - 16' 6 Bolt 11L x 15 "D"
  - 18' - 24' 6 Bolt 11L x 15 "F"
  - 27 & 30 8 Bolt 12.5 x 15 "F"
  - 36' - 50' 8 Bolt 305/70 x R22.5 Recap Truck Tire
- Tires—All Wings
  - 11L x 15 6 Bolt load range "D"

### OPTIONS

- Packer tow hitch
- Anhydrous & Liquid Tank tow hitch
- Hydraulic lines and quick coupler to tow hitch
  - from tractor remotes
  - tied into wing fold
- Axle pivot grease bank (3 section frame)
- Weight kit 100 lb (do not exceed 50 lb/ft)
- Upgrading 11L D Tire to Recap 245/70 x 19.5
- Upgrading 11L F Tire to Recap 245/70 x 19.5
- 27'-30' upgrade mainframe tires to 8 Bolt 305/70 x R22.5
- Dirt shield - help prevent soil from harrows being thrown onto the machine frame
- Cat. 5 Hitch Upgrade

\*\*Seed/Fertilizer attachment kits available, call factory for pricing

### RTS USES

- Operate in high moisture conditions
- Spring prep for no-till
- Seedbed preparation
- Incorporate cover crops
- Uniform Residue Distribution
- Stalk chopper ahead of primary tillage
- Incorporate seed-fertilizer-manure-herbicides
- All season uses
- Seeding of cereals and small grains
- Yield gain
- Use as a rotary hoe
- Perfect partner for stripper headers
- Prepare seedbed for double crop soybeans
- Warm soil and release excess moisture
- Compost heavy residue
- Release excess soil moisture
- Improve seedbeds after planting

### 3 YEAR LIMITED WARRANTY

Salford Farm Machinery is designed and built with longevity and serviceability in mind and is intended to withstand the normal rigors of agricultural use. Please talk to your dealer or call us today at (519) 485-1293 or 1-866-442-1293 for all the details. Features and specifications may change without prior notice. Please read our terms and conditions.

Osceola, Iowa • Ontario, Canada • 1-866-442-1293 • [www.salfordmachine.com](http://www.salfordmachine.com)